Online Resources

NewBasis boasts a comprehensive website that includes:

- Real time product configurator
- Downloadable product specification cut sheets
- Secure customer log-in portal
- Ability to price and track orders
- View order history

About Us

Headquartered in Riverside, CA, NewBasis has been manufacturing underground enclosure solutions for over 30 years. NewBasis utilizes state-of-the-art engineering services, providing quality production. In addition, NewBasis has a dedicated customer care staff to ensure best in class service.



Composites for Infrastructure

NewBasis

2626 Kansas Ave Riverside, CA 92507 951.787.0600 P 951.787.0632 F

newbasis.com

Send quotes to: quotes@newbasis.com

Send questions to: info@newbasis.com

Send orders to: orders@newbasis.com

©2013 NewBasis, LLC. All rights reserved. BRCH-NB002-2013














UNDERGROUND ENCLOSURES & UTILITY PADS





POLYMER CONCRETE (PCA)



MATERIAL ADVANTAGES

- Base, rings and covers are made from advanced polymer concrete composite.
- Sides and rings are fiberglass reinforced to increase durability.
- Stronger, lighter and more durable than precast concrete.
- Meets industry standard specifications.
- Internationally recognized.

| Width X | | ANSI/SCTE 77 Tier Rat | |
|-----------|--------------------------------|-----------------------|----------|
| Length | Available Depth and Body Style | T15* | T22** |
| 11" x 18" | 12" Straight | √ | √ |
| 11" x 18" | 18" Straight | √ | √ |
| 12" x 12" | 12", 24" Straight | √ | √ |
| 13" x 24" | 12", 18" Straight | √ | √ |
| 13" x 24" | 24" Straight | √ | √ |
| 17" x 30" | 12", 22", 30" Straight | √ | 1 |
| 17" x 30" | 18", 24" Straight | √ | √ |
| 24" x 24" | 12", 24" Straight | √ | √ |
| 24" x 36" | 18", 24", 30", 36" Straight | √ | 1 |
| 24" x 36" | 26", 42", 48" Straight | √ | 1 |
| 30" x 48" | 18", 30", 48" Straight | √ | 1 |
| 30" x 48" | 24", 36" Straight | √ | 1 |
| 30" x 60" | 30" Straight | √ | 1 |
| 36" x 36" | 36" Straight | 1 | 1 |
| 36" x 60" | 24", 36" Straight | 1 | 1 |
| 48" x 48" | 36", 48" Straight | 1 | 1 |
| 48" x 60" | 48" Straight | 1 | 1 |
| 48" x 96" | 48" Straight | 1 | |

• Green Dot items are available for quick-ship.

| Available Polymer Concrete Pads (PP) | | | | |
|--------------------------------------|-----------|-----------|--|--|
| 22" x 36" | 42" x 42" | 60" x 65" | | |
| 30" x 48" | 42" x 60" | 64" x 72" | | |
| 34" x 40" | 48" x 54" | 72" x 72" | | |

Polymer concrete pads are custom designed to meet the specifications of cabinet, pedestal and transformer manufacturers.


NewBasis works with customers and approving agencies to obtain necessary approvals.

Contact NewBasis customer service for your custom quote.

Moto:

- 1. Sizes and availability may vary.
- 2. Tier rating as per ANSI / SCTE 77 specification.
- 3. Enclosure accessories can be found at newbasis.com.
- *T15 loading equals 15,000 lb. test / 22,500 lb. design

FIBERGLASS (FCA)



MATERIAL ADVANTAGES

- Product includes fiberglass base with a Polymer Concrete ring and cover.
- Available straight, round and tapered.
- Available in T15 configurations.
- Higher strength to weight ratio than polymer concrete.
- Ability to make field modifications with minimal equipment.
- Tapered wall option that allows for approximately25% more internal room than straight walled equal.

| | Available Fiber Reinforced Polymer Body with Polymer Concrete Cover & Ring Assemblies (FCA) | |
|-------------------|--|--|
| Width X Length | Available Depth and Body Style | ANSI/SCTE 7 Tier Rating Tier 15* |
| 13" x 24" | 12", 18" Straight & Tapered | √ |
| 13" x 24" | 26"Tapered | √ |
| 17" x 30" | 12", 18" Straight & Tapered, 22" Straight, 26", 30" Tapered | 1 |
| 17" x 30" | 18", 24", 34" Tapered | 1 |
| 24" x 24" | 24", 30" Straight, 36" Straight & Tapered | 1 |
| 24" x 36" | 18", 30", 36", 48" Straight & Tapered, 26" Tapered | 1 |
| 24" x 36" | 24" Straight & Tapered, 42" Tapered | 1 |
| 30" x 36" | 18" Tapered | √ |
| 30" x 48" | 18", 24", 48" Straight & Tapered, 30" Straight | 1 |
| 30" x 48" | 36" Straight & Tapered | 1 |
| 30" x 58" | 18", 36" Straight | √ |
| 30" x 60" | 30", 48" Straight | √ |
| 30" x 60" | 36" Straight | √ |
| 36" x 36" | 24", 30", 36" Straight | √ |
| 36" x 60" | 18", 24", 30", 36", 48" Straight & Tapered | √ |
| 36" x 72" | 36" Tapered | √ |
| 48" x 48" | 24", 36", 48" Straight | √ |
| 48" x 60" | 36", 48" Tapered | √ |
| 48" x 72" | 30", 36", 48", 60", 72" Tapered | √ |
| 48" x 96" | 48" Straight and Tapered | √ |
| 20" x 00" | 20", 36", 42", 48" Round | √ |
| 22" x 00" | 20", 30" Round | √ |
| 24" × 00" | 36" Round | √ |
| 27" × 00" | 36" Round | √ |
| 32" x 00" | 36" Round | √ |
| 38" x 00" | 42" Round | <u> </u> |
| 40" x 00" | 30", 40", 46", 60" Round | √ |
| 54" × 00" | 36" Round | <u> </u> |
| 54" × 00" | 14", 26", 30", 38", 40", 46", 48", 60" Round | <u> </u> |

Green Dot items are available for quick-ship.

**T22 loading equals 22,500 lb. test / 33,750 lb. design

Engineering Specifications

Extensive on-site quality programs allow NewBasis to comply with virtually any standard.

Testing and Certifications
UL classified polymer concrete (BTAT.R26461) boxes and pads.
ANSI/SCTE 77, ASTM C 857, WUC 3.6 certified

Custom Solutions

NewBasis offers a comprehensive selection of molds to meet your needs.

 Accessories
 Wide selection of components that make installation of your job a snap. Customer Service

Best in class representatives that are

dedicated to servicing the customer.